



## SAFETY DATA SHEET WICKES SUPERGLUE

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME WICKES SUPERGLUE  
PRODUCT NO. 710627, 710856  
INTERNAL ID SKU 241107, 243790  
SUPPLIER BOSTIK LIMITED  
COMMON ROAD  
STAFFORD  
STAFFORDSHIRE  
ST16 3EH  
+44 1785 255141  
+44 1785 272650 (24 HOUR)  
sds.uk@bostik.com

### 2 HAZARDS IDENTIFICATION

Irritating to eyes, respiratory system and skin.

CLASSIFICATION Xi;R36/37/38.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ETHYL 2-CYANOACRYLATE	230-391-5	7085-85-0	60-100%	Xi;R36/37/38

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

#### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

#### SKIN CONTACT

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. Do not attempt to pull bonded skin apart. Any bonded skin should be well soaked in warm soapy water before attempting to gently peeled apart with the aid of a blunt object Get medical attention if irritation persists after washing.

#### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### SPECIFIC HAZARDS

Fire or high temperatures create: Toxic gases/vapours/fumes of Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Nitrous gases (NO<sub>x</sub>).

#### PROTECTIVE MEASURES IN FIRE

Wear self contained breathing apparatus

### 6 ACCIDENTAL RELEASE MEASURES

## WICKES SUPERGLUE

### PERSONAL PRECAUTIONS

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

### ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

### SPILL CLEAN UP METHODS

Provide ventilation and confine spill. Do not allow runoff to sewer. Clean-up personnel should use respiratory and/or liquid contact protection. ABSORB. Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### STORAGE CLASS

Chemical storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
ETHYL 2-CYANOACRYLATE	WEL			0.3 ppm	1.5 mg/m3

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Well-ventilated area.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

### HAND PROTECTION

Use protective gloves. Use protective gloves made of: Nitrile. Use thin cotton gloves inside the rubber gloves if allergy risk.

### EYE PROTECTION

Use approved safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Various
ODOUR	Pungent
SOLUBILITY	Polymerises in water

REVISION DATE: 12/03/2008

SDS NO.: 14947

**WICKES SUPERGLUE**

BOILING POINT (°C)	>150	RELATIVE DENSITY	1.04 - 1.1
VAPOUR PRESSURE	~0.2mm	FLASH POINT (°C)	>85

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Moisture Direct Sunlight High Temperature

**POLYMERISATION DESCRIPTION**

Avoid water.

**MATERIALS TO AVOID**

Strong oxidising substances. Water, steam, water mixtures. Alkalis Amines. Alcohols

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**11 TOXICOLOGICAL INFORMATION****INHALATION**

Irritating to respiratory system.

**INGESTION**

May cause discomfort if swallowed. May cause stomach pain or vomiting.

**SKIN CONTACT**

Irritating to skin. Product has a defatting effect on skin.

**EYE CONTACT**

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

**MARINE POLLUTANT**

No.

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**RISK PHRASES**

R36/37/38

Irritating to eyes, respiratory system and skin.

## WICKES SUPERGLUE

### SAFETY PHRASES

S2	Keep out of the reach of children
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
P3	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of reach of children.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108). Introduction to Local Exhaust Ventilation HS(G)37.

## 16 OTHER INFORMATION

### GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

### INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

### REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

### ISSUED BY

Approved EC

REVISION DATE 12/03/2008

REV. NO./REPL. SDS GENERATED 5

DATE May 2003

### RISK PHRASES IN FULL

R36/37/38 Irritating to eyes, respiratory system and skin.